

Recessed LED Trimless Downlight with Clips





2" Regular



Key Features

- 2" round or square LED trimless downlight with integral driver in connection box
- **Easy installation with spring clips or screws**
- Type IC rated-no housing needed
- Flexibility to switch color temperature during installation to suit a specific application, just adjust the color temperature with the slide switch located on the wire
- LED source SDCM<3
- **Smooth trimless look**
- Enjoy the benefits of voltage surge protection, reliable operation in low-temperature environments and longer driver lifetime
- Die-cast aluminum construction

Dimensions



Ordering Guide

Series	Wattage	Color Temperature	Voltage	Finish	
HB-2RB	8W	5CCT (2700K/3000K/3500K/4000K/5000K)	Blank AC 120V	WH (Matte White)	T Trimless
HB-2SB				BK (Matte Black)	

Example: HB-2RB8W5CCTWHT

Specifications		
Models	HB-2RB8W5CCTWHT-C	HB-2SB8W5CCTWHT-C
Applications	General lighting	
Wattage	8W	
Color Temperature(K)	5CCT	
	2700/3000/3500 /4000/5000	
Delivered Lumen(lm)	650	
Halogen Equivalent	65W	
Beam Angle	38°	
CRI	>90 (CRI 97 optional, special order)	
Driver Input	120V AC	
Power Factor	0.9	
Dimming	TRIAC dimmers 100%-10%	
Cut out	2-7/8" (72mm)	3-7/8" (100mm)
Approved Location*	Insulated ceiling, Indoor & Wet location	
Ambient Temperature	-20°C to +40°C	
Air Tight	Yes	
Projected Life	70% light output at 50,000 hours	
Certification	cETLus	
Warranty*	5-year limited warranty	

* Due to continuous improvements and innovations, specifications may change without notice

Accessories

