Recessed Fixed Downlight | Trimless Downlight with Clips



4" Round



Key Features

- 4" round LED trimless downlight with integral driver in connection box
- Easy installation with spring clips or screws
- Type IC rated-no housing needed
- Flexibility to switch color temperature during installation to suit a specific application, just adjust the color temperature with the slide switch located on the wire
- LED source SDCM<3
- Smooth trimless look
- Enjoy the benefits of voltage surge protection, reliable operation in low-temperature environments and longer driver lifetime
- Die-cast aluminum construction


	Specifications				
Models	HB-4RB15W5CCTWHT-O				
Applications	General lighting				
Wattage	22W				
Color	5CCT				
Temperature(K)	2700/3000/3500 /4000/5000				
Delivered Lumen(lm)	1900				
Halogen Equivalent	190W				
Beam Angle	38°				
CRI	>90 (CRI 97 optional, special order)				
Driver Input	120V AC (120-347V optional)				
Power Factor	0.9				
Dimming	TRIAC dimmers 100%-10% (0-10V dimming optional)				
Cut out	4-1/4" (108mm)				
Approved Location*	ion* Insulated ceiling, Indoor & Wet location				
Ambient Temperature	-20°C to +40°C				
Air Tight	Yes				
Projected Life	Life 70% light output at 50, 000 hours				
Certification	cETLus				
Warranty*	5-year limited warranty				

 $^{^{\}star}$ Due to continuous improvements and innovations, specifications may change without notice

Accessories



Dimensions



Ordering Guide

Ordering Guide Example: HB-4RB15W5CCTWHT-O								
Series		Wattage	Color Temperature	Voltage		Finish		
HB-4RB	Recessed Trimless Downlight -4" Round	22W	5CCT (2700K/3000K/3500K/4000K/5000K)	Blank	AC 120V	● WH (Matte White) ● BK (Matte Black)	T-O Trimless	