Addressable LDM-5050-RGB 24V Flexible LED Strip



Specifications

LDM-5050-RGB IC



Key Features


- 5050 LEDs: 60 LEDs per meter for bright, vibrant colors.
- Voltage: DC 24V for energy efficiency.
- Width: 10mm.
- Power: 14.4W per meter.
- IC: GS1903D for precise control.
- IP20: Suitable for indoor use.
- · Certification: cETLus certified.

Application:

- Home Decor: Accent lighting for living rooms and bedrooms.
- Retail: Product displays and highlighting features.
- Events: Dynamic lighting for parties and performances.
- Entertainment: Enhancing home theaters and gaming setups.
- Signage: Illuminating signs and displays.











Or SP108E - Wifi Magic Controller

Models	LDM-5050-RGB IC
Product Size(mm)	5000*10*0.25
LED Type	5050
Color Temperature*	RGB
Lumen/Meter	150 350 150
Input Voltage*	24V DC
Current (Amps/meter)	0.60
Min Cuttable Length(mm)	100
Max Power Consumption (Watt/m)	14.4
IC Type	GS1905A
CRI	> 90
Driver Input	120V AC
Power Factor	0.9
Dimming	Dimmable
Beam Angle	180°
LED Quantity(per meter)	60Pcs
Net Weight(kg)	0.2
Operating Temperature	-25°C~ +45°C
Storage Temperature	-30°C∼ +80°C
IP Rate	20
Estimated Life(Hours)	30,000
Certification	cETLus
Warranty	3-year

Dimensions



Linking operation:



Ordering Guide

Series		LED Type	Color Temperature	Туре	Size(Meter)
LDM	LED Strip Light	5050-60D	RGB	IC	5