LDM-5050-60D Low Voltage Flexible LED Strip



LDM-5050-60D-RGBW



Key Features

- Vibrant RGB Lighting: Equipped with 5050 LEDs for dynamic and customizable color options.
- High LED Density: 60 LEDs per meter ensure bright and consistent illumination.
- Efficient Operation: Runs at 24V DC with a power consumption of 14.4W per meter.
- Indoor Use: IP20 rating makes it ideal for dry, indoor environments.
- Safety Certified: cETLus certified, ensuring compliance with safety standards.

Application:

- Home Ambiance: Adds vibrant, customizable lighting to living spaces.
- Commercial Use: Enhances retail, restaurants, and bars with dynamic RGB effects.
- Event Decor: Ideal for colorful lighting at parties and events.
- Architectural Highlights: Accentuates indoor and outdoor features.
- Signage: Brightens signs and displays for greater visibility.







Touch Panel +Controller or


WL5 Smart Controller

Ordering Guide

Series	LED Type	Color	Rating	Size
LDM LED RGB Strip Light	5050-60D	RGBW	20	5 Meter

	Specifications
Models	LDM-5050-60D-RGBW
Product Size(mm)	5000*12*0.25
LED Type	5050 SMD LED
Color *	RIGIB W
Lumen/Meter	150 350 150 600
Input Voltage*	24V DC
Current (Amps/meter)	0.60
Min Cuttable Length(mm)	100
Max Power Consumption (Watt/m)	14.4
CRI	>80
Driver Input	120V AC
Power Factor	0.9
Dimming	Dimmable
Beam Angle	120°
LED Quantity(per meter)	60Pcs
Net Weight(kg)	0.2
Operating Temperature	-25°C∼ +45°C
Storage Temperature	-30°C~ +80°C
IP Rate	20
Estimated Life(Hours)	30,000
Certification	cETLus
Warranty	3-year

Dimensions



Linking operation:



Parallel connection is highly recommended as safe electrical operation mode.

