

Mini LED Puck Light



Key Features

- **Construction:** aluminum body with PMMA diffuser
- **Compact design:** only 1-1/4" diameter with 5/8" thickness
- **Shape:** round only
- **Easy Installation:** recessed mount
- Requires remote DC12V power supply for operation, sold separately
- Single puck and 3 pucks kit are available

Specifications	
Models	MPR
Applications	Under Cabinet
Wattage	1W
Color Temperature(K)	Single CCT 3000/4000
Lumen Output(lm)	75/95/105
Halogen Equivalent	7W
Beam Angle	120°
CRI	80
Driver Input	12V/24V DC
Power Factor	0.5
Dimming	PWM
Cut out	1-1/8" (28mm)
Approved Location*	Insulated ceiling, Indoor & Dry location
Ambient Temperature	-20°C to +40°C
Air Tight	Yes
Projected Life	70% light output at 50,000 hours
Certification	ETL
Warranty*	Project: 5-year warranty

Approved Location*-please contact our sales for outdoor application
Warranty*-refer to Hi-bright warranty policy

Accessories

12V/24V DC dimmable hardwire box



Model: LR-D12-24A 12V 24W
LR-D24-24A 24V 24W



Model: LR-D12-60S 12V 60W
LR-D24-60S 24V 60W

DC12V Wall Plug Adaptor



Quick Connector for Fast and Easy Connection



One to Six Hub



One power supply to six output for fixtures

Hand Wave Module



Wave your hand under IR sensor to turn light ON/OFF (the distance of IR sensor and your hand is 2"-10"). Stay on top of the IR sensor more than one second to adjust the brightness

Touch and Dimming Module



Tab the module to turn the light ON/OFF Touch the module more than one second to adjust the brightness

3 Pucks kit set



Ordering Guide

Example: MPL1W30K-12V-WH

Series	Wattage	Color Temperature	Voltage	Finish
MPR Hi-bright Mini Puck -Round	1W	30K (3000K-Single CCT) 40K (4000K-Single CCT)	12V 24V	<ul style="list-style-type: none"> ● WH (White) ● BK (Black)

*-Custom finishes are available