

LED Regressed Downlight Module



4"



Key Features

- 4" LED module downlight with integral driver in connection box
- Type IC rated-no housing needed
- Flexibility to switch color temperature during installation to suit a specific application, just adjust the color temperature with the slide switch located inside the J-box or on the wire
- **Aluminum interchangeable trims, round & square, reflector & baffle are available**
- LED source SDCM<3
- Aluminum construction
- **Enjoy the benefits of voltage surge protection, reliable operation in low-temperature environments and longer driver lifetime**

Specifications	
Models	HB-LED-15W-5CCT
Applications	General lighting
Wattage	15W
Color Temperature(K)	5CCT
	2700/3000/3500 /4000/5000
Lumen Output(lm)	1000
Halogen Equivalent	100W
Beam Angle	38°
CRI	>90 (CRI 97 optional, special order)
Driver Input	120V AC (120V-347V optional)
Power Factor	0.9
Dimming	TRIAC dimmers 100%-10%(0-10V dimming optional)
Cut out	3-3/4" (95mm)
Approved Location*	Insulated ceiling, Indoor & Wet location
Ambient Temperature	-20°C to +40°C
Air Tight	Yes
Projected Life	70% light output at 50,000 hours
Certification	cETLus
Warranty*	5-year

120V Input Driver Included



Accessories

Interchangeable trims



Round smooth trim



Square smooth trim

AC120V driver




Model: D415A-X (Aluminum version)

AC120-347V driver



Model: MULV15-X (Steel version)

Rough-in plate



Model: HB-MP-35

Order Example



4" module downlight

+



HB-DM-4RTWH

=



HB-DM-4STWH

