

4" Multiple Application Recessed Light


4"



Key Features

- Can be mounted to a compatible 4" recessed housing via included butterfly clips, or attached to an industry standard 4" octagon box via mounting holes.
- This fixture is fire-rated when used in a fire-rated octagon box
- A built-in, 5CCT selectable switch (2700K, 3000K, 3500K, 4000K & 5000K) enhances on-site flexibility
- Type IC rated
- Aluminum body with round iron interchangeable magnetic trims
- Interchangeable magnetic trims finishes: matte white, matte black and brushed nickel

Dimensions



Specifications	
Models	HB-4-S8W
Applications	General lighting
Wattage	8W
Color Temperature(K)	5CCT(Coming soon) 2700/3000/3500/4000/5000
Lumen Output(lm)	500/510/530/550/540
Halogen Equivalent	50W
Beam Angle	110°
CRI	80
Driver Input	120V AC
Power Factor	0.9
Dimming	TRIAC dimmers 100%-10%
Approved Location*	Insulated ceiling, Indoor & Wet location
Ambient Temperature	-20°C to +40°C
Air Tight	Yes
Projected Life	70% light output at 50, 000 hours
Certification	ETL
Warranty*	Retail: lifetime warranty Project: 7-year warranty

Approved Location*-please contact our sales for outdoor application
Warranty*-refer to Hi-bright warranty policy

Accessories

Round magnetic trim for MS-4R



Used when mounted to a compatible 4" recessed housing




Used when mounted to a compatible 4" recessed housing




Used when mounted to a fire-rated octagon junction box

Installation



4" Recessed Housing



4" Octagon Junction Box

Ordering Guide

Example: HB-4-S8W-5CCTWH

Series	Wattage	Color Temperature	Voltage	Finish
HB-4 Recessed Multiple Application Downlight -4"	8W	5CCT (2700K/3000K/3500K/4000K/5000K)	(Blank) 120V only	● WH (White)

* Other finish are available, please contact our sales to make order for special items