Bendable Extrusion Channel for LED Strip



HB-BF-213



Key Features

- Flexible & Bendable Design: Side and top bending capabilities for seamless curves, arcs, or rounded installations.
- Slim & Durable Construction: Sleek aluminum housing with excellent thermal management and protection for LED strips.
- · Dot-Free Illumination: High-quality silicone diffuser ensures smooth,
- · uniform light without visible LED dots.
- Multi-Directional Lighting: Supports side-emitting or top-emitting light depending on mounting orientation.
- Versatile Mounting: Surface or recessed installation compatible. Can follow complex shapes and architectural lines.

Application:

- · Cove and indirect lighting with seamless ceiling/wall finish
- · Curved architectural lighting designs
- · Retail, hospitality, and exhibition lighting requiring creative forms
- · Modern residential and commercial spaces


Top Bending	

Ordering Guide



	Specifications				
Models	HB-BF-213				
Dimensions:	56.48mm (W) × 13.35mm (H)				
Material:	Extruded aluminum				
Inner Width:	12.75mm				
Length:	2000mm				
Operating Temperature:	-20°C to +50°C (-4°F to +122°F)				
Compatible LED	SMD 2835 / 5050 / COB LED Strips				
LED Strip width	5mm - 8mm				
Diffuser Cover:	Milky White				
Beam Angle:	120°				
Mounting Options:	Side bending, top inside bending,				
0 P	top outside bending				
Minimum Bending Radius:	Side bending: 700 mm Top inside/outside: 300 mm				

Dimensions



Accessories





End Caps

Silicone diffusers

Series	Туре	Size	Length
HB Bendable Aluminum Profile	BF	213	2 Meter