

LDM-5050-60D Low Voltage Flexible LED Strip



LDM-5050-60D




Key Features

- Light source: 60 pcs/m SMD5050
- Material: superior and heat-resistant 10mm PCB
- Input voltage: DC 24V
- RA>80
- Lifespan: 30,000 hours
- Easy installation, cuttable and joinable, Accessories complete

Application:

- Cove lighting, Architectural lights for canopy corridor Archway,
- Backlight or edge lighting for signage DIY lights for home use
- Path and contour marking
- Decorative lights for holiday event show




DC 12-24V LED Controller and remote



Driver96W/24V

Specifications	
Models	LDM-5050-60D
Product Size(mm)	5000*10*0.25
LED Type	5050 SMD LED
Color *	R I G I B I W
Lumen/Meter	150 I 350 I 150 I 600
Input Voltage*	24V DC
Current (Amps/meter)	0.50
Min Cuttable Length(mm)	100
Max Power Consumption (Watt/m)	14.4
CRI	>80
Driver Input	120V AC
Power Factor	0.9
Dimming	Dimmable
Beam Angle	120°
LED Quantity(per meter)	60Pcs
Net Weight(kg)	0.2
Operating Temperature	-25°C~ +45°C
Storage Temperature	-30°C~ +80°C
IP Rate	20
Estimated Life(Hours)	30,000
Certification	cETLus
Warranty	2-year

Dimensions




Linking operation:

The maximum length in series is **10 meters** when led strip is DC 24V



Parallel connection is highly recommended as safe electrical operation mode.



Ordering Guide

Example: LDM-25050-600D-RGB 5M

Series	LED Type	Voltage	Color	Size
LDM	LED RGB Strip Light	5050-60D	24V	RGB
				5 Meter

* 12V, 5000K, 6000K - make to order