

Black Flexible Top View Neon LED Strip Light



NH-1010BK




Key Features

- Black neon housing, allowing flexible design for modern architectural wall panels
- Black silicone housing provides a sleek, premium appearance that blends seamlessly into dark wall finishes and panel systems
- Top-view neon light output with smooth, dot-free illumination using COB or high-density SMD technology
- Flexible top bending (vertical bending) design, ideal for shaping curves, arcs, and custom wall lighting patterns
- High CRI (>90) for accurate color rendering and refined visual quality on architectural surfaces
- 24V DC low-voltage operation, safe and reliable for residential and commercial projects


Application:

- **Decorative wall panel lighting** for feature walls and architectural surfaces
- Accent lighting for wood panels, fluted panels, stone, and modern wall cladding systems
- Interior wall detailing in residential spaces such as living rooms, hallways, and bedrooms
- Commercial wall designs in hotels, offices, restaurants, and retail environments
- Branding walls, signage outlines, and artistic wall installations
- Vertical and curved wall lighting designs requiring top-bending neon flexibility




Specifications	
Models	HB-NH-1010BK
Product Size(mm)	*10(W)*10(H)
LED Type	2835 COB
LED Quantity(per meter)	120Pcs 400Pcs
PCB Width	5 mm
Max Power Consumption (Watt/m)	7.2
Lumen/Meter	450-570
Single Color Temperature*	3000K 4000K
Current (Amps/meter)	0.3
Input Voltage*	24V DC
CRI	> 90
Lighting Direction	To View
Bending Direction	Vertical
Dimming	Dimmable
Beam Angle	120°
Min Cuttable Length(mm)	25
Net Weight(kg)	0.33
Operating Temperature	-20 °C to +50 °C
Storage Temperature	-30 °C to +80 °C
IP Rate	67
Estimated Life(Hours)	50,000
Certification	cETLus
Warranty	3-year

Dimensions



Installation Instructions - Cutting Method



Installation Options



Ordering Guide

Series		LED Type	Size	LED Type	Color Temperature	Size(Meter)
HB	LED Strip Light	NH	1010BK	2835 COB	3000K 4000K	custom size

*Due to continuous improvements and innovations, specifications may change without notice