16x16mm Silicone Flexible Neon Housing - Top View



Specifications

HB-SP1616

16mm (W) × 16mm (H)

High-quality UV-resistant Silicone

16*15mm

Top View

172

Anti-yellowing and weather-resistant

SMD 2835 / RGB/COB LED Strips

8mm or 10mm

Milky White

120

80 - 100mm

Surface mounted or recessed

-20°C~ +120°C

50 meters (customizable)

IP67 waterproof -20°C to +60°C

HB-SP1616



Key Features

- · Flexible design for curves and corners.
- · UV-resistant, non-yellowing silicone for indoor/outdoor use.
- · IP67 waterproof for reliable protection.
- · Dot-free lighting with COB or dense SMD strips.
- · Supports LED strips up to 10mm wide.
- · Easy to install with clips or channels.

D	im	er	ısi	o	n

Models

Material:

Dimensions:

Section Size

Lighting Direction

Weight(Gram/meter)

Operating Temperature:

Compatible LED Type:

Max LED Strip Width:

Installation Method:

Storage Temperature

Max Length per Roll:


Ingress Protection:

UV Resistance:


Beam Angle

Bend Radius

Color



Lighting Direction: Top View



Application:

- · Architectural contour and edge lighting (indoor & outdoor)
- Signage and channel letters illumination
- Landscape and garden accent lighting
- Facade outlines and building decoration
- Retail, hospitality, and commercial ambient lighting
- Cove, stair, and under-counter lighting with smooth dot-free effect



Clips Aluminum Profile Flexible Profile

Ordering Guide

Ordering Guide	Example: HB-SP1616-WH			
Series	Туре	Size	Color	Length
HB Silicon Flexible Profile	SP	1616	WH (Milky White)	1 Meter