

Ultra Slim LED Puck Light-Reverse CCT



Key Features

- **Construction:** plastic body with iron trim ring and PMMA diffuser, with 450mm long naked wire.
- **Slim design:** only 3" diameter with 1/4" thickness.
- **Shape:** round.
- **Easy Installation:** recessed mount & surface mount.
- Requires DC12V/ 24V dimmable driver for operation, sold separately.
- LED source SDCM<5.

Specifications

Models	UPR2W
Applications	Under Cabinet
Wattage	2.2W
Color Temperature(K)	Reverse CCT
	3000 or 4000
Delivered Lumen (lm)	150
Halogen Equivalent	15W
Beam Angle	120°
CRI	>90
Driver Input	12V DC/ 24V DC
Power Factor	0.5
Dimming	PWM
Cut out	2-1/4" (56 mm) for recessed mount
Approved Location*	Insulated ceiling, Indoor & Damp Location
Ambient Temperature	-20°C to +40°C
Air Tight	Yes
Projected Life	70% light output at 50,000 hours
Certification	cETLus
Warranty*	5-year limited warranty

* Due to continuous improvements and innovations, specifications may change without notice

Accessories

Round magnetic trim for UPR2W



12V/24V DC dimmable hardwire box




Model: DRIVER24W12V
DRIVER24W24V

Model: DRIVER60W12V
DRIVER60W24V

Only **1-1/4"**
thickness

Dimensions



Installation

