

Ultra Slim LED Puck Light



Key Features

- **Construction:** plastic body with iron trim ring and PMMA diffuser
- **Slim design:** only 3" diameter with 1/4" thickness
- **Shape:** round
- **Easy Installation:** recessed mount & surface mount
- Requires remote DC12V power supply for operation, sold separately
- Single puck and 3 pucks kit are available
- LED source SDCM<5

Accessories

Round magnetic trim for UPR2W



12V/24V DC dimmable hardwire box



Only **1-1/4"**
thickness



Specifications	
Models	UPR2W
Applications	Under Cabinet
Wattage	2.2W
Color Temperature(K)	Single CCT 3000/4000/5000
Delivered Lumen(lm)	150
Halogen Equivalent	15W
Beam Angle	120°
CRI	>90
Driver Input	12V DC (24V DC available)
Power Factor	0.5
Dimming	PWM
Cut out	2-1/4" (56mm) for recessed mount
Approved Location*	Insulated ceiling, Indoor & Damp location
Ambient Temperature	-20°C to +40°C
Air Tight	Yes
Projected Life	70% light output at 50,000 hours
Certification	cETLus
Warranty*	5-year limited warranty

* Due to continuous improvements and innovations, specifications may change without notice

Connection Wire with DC5.5 Converter & Male Daisy Chain

